



Specifications

Powered:	Yes
Amplifier Class:	D
Power Configuration:	Tri-Amped
HF Power:	40W (Continuous)
Midrange Power:	40W (Continuous)
LF Power:	60W (Continuous)
Total Power:	140W (Continuous)
HF Driver:	1" Textile Dome
Mid-Range Driver:	4" Optimized Profile, Poly Coated Paper
LF Driver:	8" Poly Coated Paper
Crossover (LF to Mid-Range:)	330 Hz
Crossover (Mid-Range to HF:)	3000 Hz
Frequency Response: (-10dB)	37Hz - 25 kHz
Frequency Range: (+/-3 dB)	45Hz - 21Hz
Listening Distance (85 dB continuous SPL with 20dB dynamic headroom)	2.8 Meters
Max SPL (Peak @ 1M):	114 dB
System THD:	<1.1% from 70 Hz to 200 Hz <0.8% from 200 Hz to 3.6kHz <1.4% from 3.6kHz to 10kHz (90dB SPL @1m)
Unbalanced Inputs:	1 x RCA
Balanced Inputs:	1 x XLR, 1 x TRS
TRS/XLR Input Sensitivity:	94dB SPL @1m (anechoic) for +4dBu input.
RCA Input Sensitivity:	94dB SPL @1m (anechoic) for -10dBV input.
Enclosure:	Front Ported
Height:	17.75 Inches (44.1 cm)
Depth:	11.25 Inches (28.5cm)
Width:	10 Inches (25.4cm)
Weight:	23 lbs (10.4 Kg)