

SPEAKERS

EZ SERIES CEILING SPEAKERS



	EZ5-10MK2	EZ8-15MK2
Impedance	8 ohms at 20 watts	8 ohms at 30 watts
Speaker Size	5 1/4" / 133.35mm	8" / 203.2mm
SPL 1W @ 1m	87dB	88dB
Freq Response ± 5dB	55Hz – 20kHz	50Hz – 20kHz
Transformer Taps	10w, 5w, 2.5w, 1.25w 8 ohm at 20w RMS	15w, 10w, 5w, 2.5w, 1.25w 8 ohm at 30w RMS
Cold Test	-25° ± 3° C 16H	
Heat Test	70° ± 3° C 16H	
Connection	4 Pin Connector for Speaker Line In/Out 5 Jumper Setting for 5 Wattage Selection	4 Pin Connector for Speaker Line In/Out 6 Jumper Setting for 6 Wattage Selection
Weight	1kg	1.5kg
Mid Range	Paper Cone	
Tweeter	13mm PEI Dome Tweeter	

EZ-PEASY INSTALLATION!



EZ5-10MK2	EZ Fit 5.25" coaxially loaded 2 Way Speaker with Silk Dome Tweeter. 100V with new Ez-TAP selector, taps at 10w, 5w, 2.5w, and 1.25w and 8 ohm setting, 88dB SPL 1w/1m. New Ez-BLOCK speaker terminals with 22uF inline supervisory capacitor, 1kg.
EZ8-15MK2	EZ Fit 8" coaxially loaded 2 Way Speaker with Silk Dome Tweeter. 100V with taps at 15w, 10w, 5w, 2.5w and 1.25w and 8 ohm setting (raw speaker has 20 watts capacity at 8 ohms). 87dB SPL 1w/1m. New Ez-BLOCK speaker terminals with 22uF inline supervisory capacitor, 1.5kg.